

# ENDURA-CRAFT® CRAFTSMAN SERIES COLUMN MATERIAL SAFETY DATA SHEET

## **A. Product Identification:**

Manufacturing Site: Pacific Columns, Inc.  
Address: 6765 Horizon Road, Heath, TX 75032  
Trade Name(s): Polyvinyl Chloride Compound (PVC),  
Endura-Craft® Craftsman Series Columns  
SYNONYMS: Vinyl Polymers, Chloroethylene homopolymer compound  
CAS Number: 9002-86-2  
MSDS Contact: Pacific Columns, Inc.  
6765 Horizon Road, Heath, TX 75032  
800-294-1098 / FAX 714-257-9628

## **B. Composition/Information on Ingredients:**

<b>Component</b>	<b>CAS Number</b>	<b>WT %</b>
Polyvinyl Chloride Resin	9002-86-2	>70%
Calcium Carbonate	1317-65-3	<10%
Titanium Dioxide	13463-67-7	<20%
Proprietary Additives	Mixture	<20%

**This product is an article as defined in 29 CFR 1910.1200. It will not result in exposure to hazardous chemicals under normal conditions of use. This product is not subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.**

## **C. Physical Data:**

Appearance (Physical form):	Finished board / Sheet (Solid)
Color:	White (unfinished)
Boiling Point, Freezing Point(°F):	Not Applicable (Solid)
Specific Gravity(H2O=1):	0.45 to 1.55
Vapor Pressure (mm Hg.):	< 0.1 (Solid)
Melting Point:	Decomposes before melting
Solubility in Water:	Solid
Vapor Density:	Solid
Evaporation Rate (Butyl Acetate):	None (Solid)
Vapor Pressure:	Not applicable (Solid)
Odor:	Odorless
PH:	Not applicable (Solid)

#### **D. Fire & Explosion Data:**

- **FLASH POINT:** Not applicable
- **AUTOIGNITION TEMPERATURE:** Not applicable
- **FLAMMABLE LIMITS IN AIR. % BY VOL.** LOWER (LEL): Not applicable  
UPPER (UEL): Not applicable
- **EXTINGUISHING MEDIA:** Dry chemical, Water spray(fog), foam, or carbon dioxide.
- **SPECIAL FIRE FIGHTING PROCEDURE:** Wear NIOSH approved, positive pressure, self-contained breathing apparatus especially in confined spaces. Full protective clothing. Evacuate all personnel from danger area.
- **UNUSUAL FIRE AND EXPLOSION HAZARD:** PVC will not continue to burn without an external fire source. The gaseous products of PVC combustion are hydrogen chloride, carbon monoxide, carbon dioxide and other toxic gases. Exposure to combustion products may be fatal and should be avoided.

#### **E. Health Hazard Information:**

**(Pertains to dust or chips generated during fabrication processes on finished trim boards and sheet)**

##### **First Aid:**

- **Eyes:** Immediately flush with plenty of water for a period of 15 minutes. Do not rub eyes. If irritation persists consult a physician.
- **Skin Contact:** Flush skin with plenty of water. Remove contaminated clothing. Wash clothing before reuse. If irritation persists immediately consult a physician.
- **Skin Absorption:** No absorption is likely to occur in its solid form.
- **Inhalation:** If respiratory irritation exists, remove to fresh air.
- **Ingestion:** Although unlikely under normal conditions and use, if ingestion occurs seek medical attention. Please reference section D, Fire and Explosion Data.
- **Medical Conditions Aggravated by overexposure:** Available toxicological data and the physical and chemical properties of the product suggest that there is no evidence that this product will aggravate an existing medical condition.
- **Note to Physician:** Treat symptomatically and supportively.
- **Other Instructions:** Never give anything by mouth to an unconscious person.

##### **NATURE OF HAZARD:**

- **EYES:** If exposed to high concentrations of dust, physical irritation of the eyes.
- **SKIN:** This material is not expected to present a hazard to the intact skin. Molten sheet will produce thermal burns.
- **INHALATION:** Under normal conditions and with normal use, no inhalation hazard is presented. Please refer to Section D, Fire and Explosion Data.
- **INGESTION:** No significant health hazard can be reasonably anticipated.

## **EXPOSURE LIMITS:**

- None established.
- ACGIH TLV of 10 mg/m<sup>3</sup> total dust as an 8-hour TWA is recommended.
- OSHA – PEL: Not applicable

## **TOXICITY DATA:**

- SKIN CONTACT: A review of the pertinent literature did not reveal specific information for PVC.
- EYE CONTACT: A review of the pertinent literature did not reveal specific information for PVC.
- INHALATION: Rodents exposed by the dietary or inhalation route for 6 to 24 months have shown no significant toxicological effects.
- INGESTION: See above.
- SPECIAL PRECAUTIONS - AVOID INHALATION OF COMBUSTION PRODUCTS.

## **F. Reactivity Data:**

CONDITIONS CONTRIBUTING TO:

INSTABILITY: Not applicable

INCOMPATIBILITY: Not applicable

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, hydrogen chloride and other toxic fumes generated with combustion.

HAZARDOUS POLYMERIZATION: Will not occur. Not applicable.

## **G. Spill or Leak Procedure:**

When producing chips or dust from fabricating PVC sheet, sweep, scoop, or vacuum and remove. Dispose of only in accordance with local, state, and federal regulations. Recycling of PVC sheet and boards should be encouraged whenever possible.

## **H. Special Protection Information:**

**\*\*Pertains to dust or chips as a by-product of fabricating finished sheet\*\***

- VENTILATION RECOMMENDATIONS - General ventilation when fabricating and nuisance dust control.
- SPECIFIC PERSONAL PROTECTIVE EQUIPMENT
- RESPIRATORY PROTECTION: If dust is produced during handling, an approved particulate filter respirator should be used.
- EYES: Safety glasses or goggles.
- GLOVES: Wear gloves when cutting or fabricating sheets or trimboards. Use gloves when handling hot or molten sheet.
- Required Work: Do not eat, drink or smoke in work area.
- Hygiene Procedure: Wash hands thoroughly after handling, especially before eating, drinking, smoking, chewing, or using restroom facilities.
- OTHER CLOTHING AND EQUIPMENT: As necessary when handling hot or molten sheet.

**I. Shipping Transfer & Storage:**

- SHIPPING INFORMATION - Non-hazardous for transportation purposes.
- TRANSPORTATION AND STORAGE
  - USUAL SHIPPING CONTAINERS: Palletized sheets
  - STORAGE TRANSPORT: Store in a cool, dry, well ventilated area, away from sources of extreme heat or fire. Temperatures above 150°F may cause slow product degradation.
  - ELECTROSTATIC ACCUMULATION HAZARD: Yes
  - DOT Shipping Name – Not Listed
  - DOT Label – Not Applicable
  - DOT Hazard Glass – Not Regulated
  - UN/NA Number – Not Applicable
  - Hazard Labels/Placard(s) – Not Applicable
  - Packing Group – Not Applicable
  - Bulk Packaging – Not Applicable
  - RQ – Not Applicable
  - ERG No. – Not Applicable

**J. Ecological Information:** No data is available on the adverse effects of this product on the environment.

HFPA	HMIS
Fire - 1	Health – 0
Health - 0	Flammability – 1
Reactivity - 0	Reactivity – 0
Specific Hazard – None	Personal Protection Index - E

**K. Disclaimer Liability:**

The above data is based upon tests performed for, and experience of Turncraft Architectural or Turncraft Architectural suppliers and is provided for informational purposes only. Turncraft Architectural products are intended for sale to industrial and commercial customers. Turncraft Architectural requests that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Turncraft Architectural disclaims any liability for damage or injury which results from the use of the above data and nothing contained therein shall constitute a guarantee, warranty (including warranty of merchantability) or representation (including freedom from patent liability) by Turncraft Architectural with respect to that data, the product described, or their use for any specific purpose, even if that purpose is known to Turncraft Architectural. Compliance with all applicable Federal, State, and Local laws and regulations remains the responsibility of the user.

Dated: March 11, 2005